

**NEW!**


# EASY LOADING

**Ideal for  
street markets  
and food shops:**

- 1. Easy loading:** 2" receipt printer for immediate change of paper roll.
- 2. Long-lasting internal battery** (up to 52 hours of autonomy).
- 3. Mechanical keyboard** (10 vendors, 99 direct PLUs and 999 from the keyboard).
- 4. Restyling:** 7" LCD segment display and oval column, more modern and attractive.



## Dimensions



DATA IN mm

<b>A</b>	375
<b>B</b>	470
<b>C</b>	140
<b>D</b>	580

Plate dimensions:  
L360 x W280 mm.  
Weight with packaging: 12.0 kg.



**EASY LOADING**  
RECEIPT PRINTER




**LCD SEGMENTS**  
DISPLAY



**UP TO**  
**10.000 PLUs**



**UP TO**  
**10 VENDORS**



**ETHERNET**  
TCP/IP



**INTERNAL RECHARGEABLE**  
**BATTERY**



**METROLOGICAL**  
**VERIFICATION**  
OPTIONAL (EU)

new **D-500 EASY LOADING**

# Characteristics and functionality

## Features

- Extensive information for each PLU: normal price and offer price, price for weight scales and by kg/100 g, 3 names of 20 characters or 2 names of 30 characters, 20 free texts of 24 characters, 1 text of 3,072 characters, etc.
- PLU search by code or name.
- Preset keys to programming menus: to change prices, register PLUs or vendors, etc.
- Direct access to 999 PLUs from the keyboard.
- Drill down menus.
- Printing of the scale menus.
- Programmable macros: recording of a sequence of keys to create direct access to any task (reopening of receipt, lists, change in batcher number, etc.).
- Sales and management reports: sales (by article, vendor, time frames, last month, etc.), margins, balance available in the cash drawer, modified PLUs, etc.
- Fast and reliable communication between scales, with PC and mobile devices (via DWS).
- Stocks management on the scale.
- Stock / order mode.
- 10 types of generic traceability (for meat, fish, fruit, vegetables, etc.) up to 99 products. Included in the prevailing European legislation on bovine traceability.

## Capacity / Accuracy

- Multi-range (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g or 15 kg / 5 g - 30 kg / 10 g.
- Mono-range (3,000 divisions): 30 kg / 10 g or 15 kg / 5 g.
- Mono-range (6,000 divisions): 12 kg / 2 g or 30 kg / 5 g.

## Format

- Double body.

## Construction

- Highly resistant ABS plastic casing.
- Stainless steel plate.
- Access to all non-metrological components without the need to unseal the scale.

## Display

- 7" backlit LCD segment displays for vendor and buyer (showing weight, price / kg, amount, tare, vendor and name of the article, occupied memory indicators and real-time subtotal detail).

## Printer

- Receipt printer for immediate change of paper roll.
- 54 mm thermal printer.
- Resolution: 8 dots/mm.
- Speed: 50 mm/s.

## Receipts

- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- Up to 75 items.
- 2 fixed formats + 2 programmable formats.
- Barcodes: EAN-13, EAN-128, Code 128 and QR.
- Name of vendor.

- 9 payment methods.
- Total in national currency and another 3 currencies.
- Discounts per line and total.
- Loyalty points.
- Customers on account.
- Recipes.

## Food information

- Minimum letter size: 1.2 mm.
- Effect (**bold**, underlined or **both**) for each character in the text.
- Possibility of using the general text "G" (3,000 characters) for ingredients.
- Possibility of including a table of nutritional facts.
- Free texts (20 x 24 characters).
- For direct sale receipts and labels: possibility of indicating in the PLU name (with an \* or other symbol) those that contain allergens and programming a text, such as "\* Consult allergens".

## Communications

- TCP/IP Ethernet for interconnection and connection to PC.

## Security

- Access to different protected programming menus via configurable passwords.

## Interconnection

- Up to 10 scales per section.

## Connectivity with other devices

- PC.
- Cash drawer (RJ11).

## Software

- DFS:
  - > Programming of scales.
  - > Receipt of sales data.
  - > Data backup copy.
  - > Graphic design of receipts and labels (DLD).
- Integration tools: in Windows or Linux to facilitate communication with the Back-Office.

## Power supply

- Mains: 110 up to 230 VAC.
- High-performance internal rechargeable battery: up to 52 hours of autonomy (calculated for 1,500 receipts, with 3 items per receipt)\* and connector to external 12 V battery.

## Energy consumption

- 6,5-91 W (depending on the conditions of use).



\* With backlight switched off. Charging times and autonomy may vary considerably depending on the temperature, age and condition of the batteries, use of the backlight, frequency of use of the printer, interconnection, etc.