

Reliable and easy to use AISI 304 stainless steel crane scales suitable for indoor and outdoor use, for industrial weighing applications. Reduced lifting distance of the crane.

The single security system makes them suitable for lifting and weighing the load.

IP67 protection from dust and rain. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights..



FEATURES

- Single security system, for the lifting and the weighing of the load.
- In compliance with the directives 2006/42 CE, UNI EN 13155/2009, UNI EN 13889, 2014/30/EU.
- Large backlit 25mm LCD display easily visible in all lighting conditions and also with low temperatures.
- Fitted with standard approved upper galvanized shackle and standard approved bottom hook.
- GR3 and GOC1 for MCWR2 (150/300/600/1500).
- Reduced distance between the upper shackle and bottom hook.
- Precision: +/- 0.05% F.S.
- Waterproof keyboard with 5 keys: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- MODE-key configurable as:
- PEAK (maximum value read), HOLD (blocking the weight viewed), Weighs accumulation, lb/kg/N conversion.
- See the user manual for the list of the functions.
- IP67 stainless steel case.
- Fitted with remote control for up to a 8 m distance. The remote control may be configured by the customer as automatic tare only, or as a remote keypad.
- Rechargeable sealed battery with a 40-hour life battery. On request, it is available a second battery for a 24/7 use.
- Equipped with 230Vac 50 Hz battery charger.
- Operating temperature: -10 /+40 °C.
- Programmable digital filter and auto switch-off.

Available versions

Code	Max (kg)	d (kg)	M (kg)
G200P300	300	0,1	--
G200P600	600	0,2	--
G200P1500	1500	0,5	--
G200P150M	150	--	150
G200P300M	300	--	300
G200P600M	600	--	600
G200P1500M	1500	--	1500

OPTIONS (ONLY AT TIME OF ORDER)

- 868MHz radio frequency module complete with TTL output. Maximum operating distance under suitable environmental and installation conditions: 70m indoor, 150m outdoor. Maximum 50 configurable channels.
- • Integrated Bluetooth interface. For wireless connection to a computer, smartphone or laptop. Downloadable weighing application from Google Play.
- • Rechargeable battery kit with integrated charging circuit. In place of the AA battery drawer. Complete with power supply with EU-UK-US socket. Accessory not available separately, must always be combined with the instrument at the time of order
- • Alibi memory (fiscal memory, maximum 120,000 weights) for the approved transmission of the weight to PC / PLC or storage in MMC / USB. Integrated clock / calendar for date / time printing with PCBs, terminals, plastic box and labels with the UL mark (if present).

FUNCTIONS AVAILABLE BY THE REMOTE CONTROL

- Standard: Infrared remote control with 19 keys (standard), operation up to 8m: zero; tare / manual tare; enable / disable function; Print; off.
- Optional: Radio remote control with 6 keys (optional), operation up to 50m: zero; tare; enable / disable function; Print; off.

ASSWM PC program "WeiMonitor"

To monitor and record the weighings carried out on the connected scale, in real time.

✓ Data	✓ Ora	✓ Netto	✓ Lordo	✓ Tara
27/03/2012	18:23:56	1.369kg	1.369kg	0.000kg
27/03/2012	18:24:09	2.094kg	2.094kg	0.412kg
27/03/2012	18:24:13	1.620kg	2.094kg	0.473kg
27/03/2012	18:24:21	1.342kg	2.094kg	0.752kg
27/03/2012	18:24:33	0.665kg	1.079kg	0.414kg
27/03/2012	18:24:50	1.846kg	2.957kg	0.663kg
27/03/2012	18:24:59	1.702kg	1.702kg	0.000kg
27/03/2012	18:25:05	2.907kg	2.907kg	0.000kg
27/03/2012	18:25:09	2.094kg	2.094kg	0.000kg
27/03/2012	18:25:20	1.369kg	1.369kg	0.000kg

BATTERY KIT FOR 24/7 USE

