

Stainless steel digital crane scale with IP67 protection against dust and sprays, 40mm DOT LED large display, for maximum visibility from all angles and in any lighting condition, even direct sunlight.

The single security system makes them suitable for lifting and weighing the load.

Sturdy and reliable, usable indoors as well as outdoors. Minimum reduction of the crane's lifting space. The models with up to 15000 kg capacity are fitted with test certificate obtained with sample weights, for higher capacities the certificate is available on request.



FEATURES

- Single security system, for the lifting and the weighing of the load.
- In compliance with the directives 2006/42 CE, UNI EN 13155/2009, UNI EN 13889, 2014/30/EU.
- Extremely bright large red DOT LED 40mm display, which guarantees a perfect visibility of the weight from any angle, also from a long distance with direct sunlight.
- Usable indoors as well as outdoors, great visibility also in full sunlight.
- Adjustable brightness intensity.
- Sturdy STAINLESS steel structure, with IP67 protection degree of the load cell and the electronics, against dust and sprays.
- Extremely reduced distance between upper and lower shackles.
- Precision: +/- 0,05% on F.S. for 3T to 9T models
- Precision: +/- 0,1% on F.S. for 12T to 50T models
- 5-key waterproof keypad: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- Programmable digital filter, for an excellent weight display in any working condition.
- Programmable automatic switch-off function, either through keypad or remote control.
- Rechargeable battery, with an average life of about 30 hours.
- Configured for a second optional extractable battery for 24/7 continuous use.
- Programmable digital calibration and Set-Up directly from the keypad or from PC through Dinitools.
- Operating temperature range: -10/+40 °C.

Available versions

Code	Max (kg)	d (kg)	M (kg)
G200PT3M M	3000	1	1
G200PT6M M	6000	2	2
G200PT9M M	9000	5	5
G200PT12	12000	5	--
G200PT17	15000	10	--
G200PT25	25000	10	--
G200PT30	30000	20	--
G200PT50	50000	20	--

CRANE SCALE: SELECTABLE FUNCTIONS

- PEAK (maximum value read).
- HOLD (lock of the displayed weight).
- Weighing totalization.
- lb/kg/N conversion (see DFW weight indicators for more functions).
- +/- checkweighing.
- Percentage weighing.
- Counting.
- Peer-to-peer.
- High Resolution Weighing x 10.
-

CRANE SCALE: OPTIONS (ONLY AT TIME OF ORDER)

Radio frequency weight transmission to remote indicator, up to 70m indoors.

868Mhz radio interface.

WI-FI interface.

Remote weight indicator connected in radio frequency, with the printer or other accessories.

ACCREDIA calibration certificate according to OIML/ASTM standards.

ASSWM PC program "WeiMonitor"

To monitor and record the weighings carried out on the connected scale, in real time.

✓ Data	✓ Ora	✓ Netto	✓ Lordo	✓ Tara
27/03/2012	18:23:58	1.309kg	1.369kg	0.000kg
27/03/2012	18:24:09	2.094kg	2.094kg	0.412kg
27/03/2012	18:24:13	1.620kg	2.094kg	0.412kg
27/03/2012	18:24:21	1.343kg	2.094kg	0.750kg
27/03/2012	18:24:33	0.665kg	1.079kg	0.414kg
27/03/2012	18:24:50	1.846kg	2.957kg	0.663kg
27/03/2012	18:24:59	1.702kg	1.702kg	0.000kg
27/03/2012	18:25:05	2.607kg	2.607kg	0.000kg
27/03/2012	18:25:09	2.094kg	2.094kg	0.000kg
27/03/2012	18:25:20	1.309kg	1.369kg	0.000kg

BATTERY KIT FOR 24/7 USE

