



NEW



Discover more details and matching accessories online!

## Robust bench scale with IP68/IP69K protection and checkweighing display, with optional verification

### Features

- Dust and splash water protection type IP68/ IP69K. Therefore very robust and durable. Ideal for rough environmental conditions
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Rechargeable battery pack and power supply included with delivery for continuous operation of the scale, even during charging
- Thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations
- Innovative weighing with tolerance range: The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning, dosing and grading

- Integrated piece-counting function with storable piece weight
- Sleep function: The scale automatically switches to energy-saving mode after an adjustable period of inactivity


### Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 190×230 mm
- Overall dimensions WxDxH 288×233×102 mm
- Net weight approx. 2,2 kg
- Internal rechargeable battery pack, operating time up to 500 h without backlight, charging time approx. 4 h
- Permissible ambient temperature -10 °C/40 °C

### Main scope of applications

- Food industry
- Chemical industry
- Pharmaceutical industry

### STANDARD



### OPTION



### FACTORY



### Model

### Weighing capacity [Max]

**KERN**

kg

### Readability [d]

g

### Verification value [e]

g

### Minimal load [Min]

g

### Smallest part weight (Normal)

g/piece

### Options

### Verification

### Options

### Calibr. Certificate

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Smallest part weight (Normal)	Options	
						DAkkS	KERN
<b>FPB 3K-4</b>	3	0,2	-	-	2	-	963-127
<b>FPB 6K-3</b>	6	0,5	-	-	5	-	963-128
<b>FPB 15K-3</b>	15	1	-	-	10	-	963-128
<b>FPB 30K-3</b>	30	2	-	-	20	-	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order.

The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

<b>FPB 3K-3M</b>	3	1	1	20	10	965-227	963-127
<b>FPB 6K-3M</b>	6	2	2	40	20	965-228	963-128
<b>FPB 15K-3M</b>	15	5	5	100	50	965-228	963-128
<b>FPB 30K-2M</b>	30	10	10	200	100	965-228	963-128